



Technical data:
EOB 150K50

Construction	
Cable length of display device:	1,800 m
Casing material:	plastic
Dimensions of display device (WxDxH):	213 mm x 110 mm x 45 mm
Dimensions of weighing plate (WxDxH):	315 mm x 305 mm x 55 mm
Material weighing plate:	stainless steel
Weighing surface (WxD):	314,500 mm x 304,500 mm
Service	
Adjustment at the location of installation:	961-249
DAkkS Certificate:	963-129
Display	
Display digit height:	25 mm
Power supply	
Input voltage:	220 V - 240 V AC 50 Hz
Operating time:	60 h
Functions	
Data hold function:	yes
Vibration-free weighing (Animal weighing program):	yes

Measuring system	
Adjustment options:	External calibration
Linearity:	100 g
Readout [d]:	50 g
Recommended adjusting weight:	100 kg (M2)
Reproducibility:	50 g
Resolution:	3000
Stabilisation time:	3 s
Tare range:	150 kg
Warm up time:	10 min
Weighing range [Max]:	150 kg
Weighing system:	Strain gauge
Weighing units:	kg
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	10 °C

EOB 150K 50

WEIGHTING RANGE (Max) Kg	150
READOUT (d) g	50
REPRODUCIBILITY g	50
LINEARITY g	± 100
NET WEIGHT approx. Kg	4.8

AVAILABILITY : 2 weeks on receipt of payment

Delivery : by international courier (on application)

Payment terms : In advance by Bank wire transfer in GBP (£ Sterling) only.